

Hygro-thermometer

Pocket type hygro-thermometer 8701/03/05



8701



8703



8705

- ▲ SIMULTANEOUSLY DISPLAY TEMPERATURE AND HUMIDITY
- ▲ EASY-TO-READ DUAL LCD DISPLAY
- ▲ DESIGN WITH CAPACITANCE TYPE RH SENSOR TO GET ACCURATE AND QUICK READING
- ▲ MAXIMUM / MINIMUM AND RESET FUNCTION
- ▲ TEMPERATURE UNIT °C/°F SELECTABLE
- ▲ HOLD FUNCTION TO FREEZE CURRENT READING
- ▲ ENTIRE LCD FLASH TO INDICATE LOW BATTERY STATUS
- ▲ SLEEP MODE CAN BE DISABLED
- ▲ SENSOR CAP TO PROTECT SENSOR
- ▲ PACKET CLIP DESIGN FOR EASY PORTABLE AROUND
- ▲ LIGHT WEIGHT AND LONG BATTERY LIFE
- ▲ 8703 FEATURES DEW POINT TEMPERATURE DISPLAY
- ▲ 8705 FEATURES DEW POINT & WET BULB TEMPERATURE DISPLAY

Model	8701	8703	8705
Temp. range	-10~50°C	-20~50°C	-20~50°C
Temp. resolution		0.1°C/°F	
Temp. accuracy		+/-1°C	
Humidity. range	5%~95%RH	0%~100%RH	0%~100%RH
Humidity resolution		0.1%RH	
Humidity accuracy	+/-4%RH at 25°C	+/-3%RH (at 25°C, 10~90%RH, others +/-5%RH)	
Dew point range	N/A	-68.5~50°C	-78.7~50°C
Wet bulb range	N/A	N/A	-21.6~50°C
Response time	80 seconds typical	60 seconds typical	
Self calibration	N/A	N/A	N/A
Battery Life		>500 hours	
LCD size (mm)		18(H)x29(W)	
Storage temp.		-20~50°C	
Storage RH%		Humidity < 90%	
Dimension(mm)		170x48.5x16.5(H)	
Weight		~75g	
Battery		AAA x 2pcs	
Standard Package	Meter/Battery/Manual/Paper box		